

### REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1-10 in the underlying PCT Application No. PCT/DE02/03975 and adds new claims 11-21. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter). The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE02/03975 includes an International Search Report, dated July 2, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

*by [Signature] (n 226091)*

Dated: 2 July 2001

By: \_\_\_\_\_  
Richard L. Mayer  
Reg. No. 22,490

One Broadway  
New York, NY 10004  
(212) 425-7200  
(212) 425-5288

CUSTOMER NO. 26646

## SENSOR ELEMENT

~~Background Information~~ FIELD OF THE INVENTION

The present invention ~~is based on~~ relates to a sensor element ~~according to the definition of the species in Claim 1.~~

5

BACKGROUND INFORMATION

A gas probe having such a sensor element is ~~known from the~~ described in German Patent Application No. DE 198 57,468 ~~At~~ 57 468, for example, for use in analyzing the exhaust gas of internal combustion engines. In a conventional manner ~~known to one skilled in the art~~, the elongated planar sensor element is arranged in a housing that can be affixed in a measuring orifice of an exhaust pipe. On the measuring side, at an end that is exposed to the exhaust gas, the sensor element has a measuring device, which includes an electrochemical cell having a first electrode, a second electrode and a solid electrolyte situated between the first and second electrode. The first electrode is arranged in a reference-gas region introduced in the sensor element. The second electrode is mounted on an outer surface of the sensor element and is in contact with the exhaust gas via a porous protective layer.

A heating device is provided to heat the measuring device. The heating device has a meander-shaped heater (resistance heater) to which a first and a second heater supply lead are guided. The heater supply leads electrically connect the heater, which is arranged on the measuring-side end of the sensor element, to contact surfaces provided on a

connection-side end lying across from the measuring-side end of the sensor element and via which the heater is electrically connected to electrical circuit elements arranged outside of the gas sensor. The heater and the two heater supply leads are arranged in a plane of stratification of the sensor element. The two heater supply leads extend in parallel to the longitudinal axis of the sensor element. Insulation layers electrically insulate the heating device from the surrounding elements.

The heater is operated in a conventional manner by the electrical circuit elements applying a voltage between the two heater supply leads. The first heater supply lead is at a constant potential, such as earth potential. ~~It is known to determine~~ Conventionally, the temperature inside the measuring device is determined with the aid of a resistance measurement, for example, and to control the heating device with the aid of the electrical circuit elements in such a way that a predefined temperature value is given inside the measuring device. The control-related potential changes at the second heater supply lead may interfere with the function of the measuring device because of induced voltage. Therefore, an electron-conducting intermediate layer, made of platinum, for example, is provided between the heating device and the measuring device, the intermediate layer being at a constant electrical potential.

It is disadvantageous in this context that the layer configuration for reducing the voltages which the heating device induces into the measuring device is expensive to produce and the additional platinum layer is costly.

~~Summary of the Invention~~ SUMMARY

~~In contrast to the related art, the~~ An example sensor

element according to the present invention, ~~having the~~  
~~characterizing features of the independent claim, has~~ may  
have the advantage of realizing a layer configuration by  
which an impairment of the measuring device due to induced  
5 voltages is reduced, or avoided entirely, in a  
material-saving and simple manner. To this end, a first  
heater supply lead, which is at an at least largely constant  
potential, is arranged in a plane of stratification between  
a second heater supply lead and the measuring device. The  
10 first heater supply lead thus functions as connection lead  
of the heater and simultaneously shields the measuring  
device from induced voltages of a second heater supply lead  
that result from changes in the potential of the second  
heater supply lead occurring during operation.

15 ~~The measures specified in the dependent claims permit~~  
~~advantageous further refinements and improvements of the~~  
~~sensor element indicated in the independent claim.~~

20 If the first heater supply lead covers the full surface of  
at least one supply region of the sensor element, the  
measuring device is shielded from the second heater supply  
lead in an especially effective manner. To save material,  
the first heater supply lead may form a lattice structure.

25 The first heater supply lead ~~is~~ may be advantageously  
arranged in such a way that the perpendicular projection of  
the second heater supply lead onto the plane of  
stratification of the first heater supply lead lies on the  
30 first heater supply lead, at least regionally.

In an especially advantageous manner, using screen printing  
and the indicated sequence, the following layers are applied  
onto a carrier foil: a second insulation layer by which the

second heater supply lead and the heater are insulated from the carrier foil; the heater and the second heater supply lead; a first insulation layer by which the first heater supply lead is insulated from the second heater supply lead; the first heater supply lead; and, if appropriate, a third insulation layer, which covers the first heater supply lead. The first heater supply lead is printed directly onto a contact region of the heater and is thus electrically connected to the heater. For this reason, a recess is provided in the contact region of the heater in the first insulation layer. After printing, the carrier foil is laminated to one or a plurality of solid electrolyte foils of the measuring device, and then sintered.

As an alternative, the second insulation layer, the heater and the second heater supply lead may be applied onto the carrier foil by means of screen printing. The first heater supply lead and, if appropriate, the third insulation layer are printed onto an insulation foil using screen printing. The first heater supply lead is electrically connected to the heater by a plated through-hole in the insulation foil. After printing, the carrier foil, the insulation foil and one or a plurality of solid electrolyte foil(s) of the measuring device are laminated and then sintered.

~~Brief Description of the Drawing~~ BRIEF DESCRIPTION OF THE DRAWINGS

The present invention ~~will be~~ is explained with reference to the drawings and the following description.

~~The figures show:~~

Figure 1 shows an exploded view of a partial region of a

first exemplary embodiment of a sensor element according to the present invention.

Figure 2 shows a cross section, along line II - II in Figure 1, through the first exemplary embodiment of the sensor element according to the present invention, ~~and~~.

Figure 3 shows an exploded view of a partial region of a second exemplary embodiment of a sensor element according to the present invention.

~~Description of the Embodiments~~ DETAILED DESCRIPTION OF  
EXAMPLE EMBODIMENTS

Figures 1 and 2 show a first exemplary embodiment of the sensor element according to the present invention. Sensor element 10 has a heating device 21, which is applied on a carrier foil 20, and a measuring device 22. Measuring device 22 of sensor element 10 is not shown in Figure 1.

Measuring device 22, which is arranged on the measuring-side at an end 26 of sensor element 10 that is exposed to the exhaust gas, has a first solid electrolyte foil 61 and a second solid electrolyte foil 62. A reference-gas region 63 containing a reference gas has been introduced in first solid electrolyte foil 61. To this end, reference-gas region 63 is in connection with the atmospheric air via a channel in a supply region 25 of sensor element 10. In reference-gas region 63, a first electrode 64 is affixed on second solid electrolyte foil 62. A second electrode 65, covered by a porous protective layer 66 and exposed to the exhaust gas, is situated across from first electrode 64 on the outer surface of second solid electrolyte foil 62. First and second electrode 64, 65 and second solid electrolyte foil 62 form a Nernst cell. Using the voltage generated between

electrodes 64, 65 in the Nernst cell, it is possible to infer the oxygen partial pressure in the exhaust gas.

However, the present invention is not restricted to a sensor element having a measuring device of the afore-described configuration. The measuring device may also include a pump cell, a combination of pump and Nernst cell (broadband lambda sensor) or some other combination of electrochemical cells. The measuring device may also have a design that realizes another measuring method, such as a resistive measurement.

Measuring device 22 is heated by heating device 21 and maintained at a constant temperature. On the basis of a temperature inside sensor element 10 detected with the aid of measuring device 22, heating device 21 is controlled by electrical circuit elements arranged outside of sensor element 10. Heating device 21 includes a heater 30, which is configured as meander-shaped resistance heater, and a first and a second heater supply lead 31, 32 arranged in supply region 25 of sensor element 10 and electrically connected to heater 30. First and second heater supply lead 31, 32, via a first and second plated through-hole 51, 52, respectively, and via a contact surface in each case (not shown) on an outer surface of carrier foil 20, connect heater 30 to the electrical circuit elements in carrier foil 20. For the heating of measuring device 22, the electrical circuit elements apply a voltage between first and second heater supply lead 31, 32. First heater supply lead 31 is constantly at earth ground potential; and heater 30 is energized or de-energized by a change in the potential of second heater supply lead 32.

Connecting the potential of second heater supply lead 32 may



cause interference in the measuring signal of measuring device 22 due to induced voltage. To avoid induced voltages, first heater supply lead 31 is arranged in a plane of stratification between second heater supply lead 32 and measuring device 22. To this end, first heater supply lead 31 is drawn across the entire large area of sensor element 10 in supply region 25. In contrast, the width of second heater supply lead 32 is less than the corresponding width of sensor element 10. Provided between first and second heater supply lead 31, 32 is a first insulation layer 41, by which the two heater supply leads 31, 32 are electrically insulated from one another. Second heater supply lead 32 forms a continuous printed circuit trace with heater 30. First heater supply lead 31 is electrically connected to heater 30 at a contact point 45 in whose region first insulation layer 41 has a recess. A second insulation layer 42 insulates heating device 21 from carrier foil 20, and a third insulation layer 43 electrically insulates it from measuring device 22.

The sensor element is produced using screen-printing technology. Printed (in this sequence) onto carrier foil 20 for this purpose are second insulation layer 42; heater 30 having contact point 45 and second heater supply lead 32; first insulation layer 41; first heater supply lead 31; and third insulation layer 43. The electrical connection of heater 30 to first heater supply lead 31 is implemented by printing the one end of first heater supply lead 31 directly onto contact point 45 of heater 30. For this purpose, a recess is provided in this region in first insulation layer 41. Printed carrier foil 20 is laminated together with solid electrolyte foils 61, 62 of measuring device 22 and then sintered.

With the exception of the recess in the region of contact point 45 for contacting heater 30 and first heater supply lead 31, first insulation layer 41 may also extend across the entire large surface of sensor element 10, that is, it may also be provided in the region of heater 30. First heater supply lead 31 may likewise extend into the region of heater 30.

Figure 3 shows a second exemplary embodiment of the sensor element according to the present invention in which mutually corresponding elements are identified by reference numerals matching those in Figure 1. The second exemplary embodiment differs from the first exemplary embodiment shown in Figure 1 in that, to insulate first from second heater supply lead 31, 32, no printed first insulation layer 41 is used, but an insulation foil 44 similar to carrier foil 20. In this way, insulation foil 44 separates first heater supply lead 31 from heater 30 and from second heater supply lead 32. Insulation foil 44 extends across the entire large surface of the sensor element. The contacting of heater 30 to first heater supply lead 31 is implemented via a third plated through-hole 53 introduced in insulation foil 44.

To produce the second exemplary embodiment of the sensor element, the following are printed (in this sequence and using screen-print technology) onto carrier foil 20: second insulation layer 42, heater 30 having second heater supply lead 32. First heater supply lead 31 and third insulation layer 43 are printed onto insulation foil 44. After printing, carrier foil 20 and insulation foil 44 are laminated together with solid-electrolyte foils 61, 62 of measuring device 22 and then sintered. First heater supply lead 31 may also extend into the region of heater 30 or across the entire large surface of sensor element 10.

In another ~~specific development~~ embodiment of the present invention (not shown), the heater may be arranged in the same plane of stratification as the first heater supply lead, which is at a constant potential, and/or it may form a continuous circuit trace with the first heater supply lead, while the second heater supply lead is provided in a plane of stratification on the side of the first heater supply lead facing away from the measuring device. For the contacting of the second heater supply lead to the heater, a contact point or a plated through-hole is provided as it is in the specific developments shown in the figures.

Heater 30 and first and second heater supply leads 31, 32 have platinum with a ceramic portion, for instance. The main component of first, second and third insulation layer 41, 42, 43 is aluminum oxide, for example. First and second solid electrolyte foil 61, 62 are made mainly of yttrium-stabilized zirconium oxide. Carrier foil 20 and insulation foil 44 include, for instance, yttrium-stabilized zirconium oxide and/or aluminum oxide. If carrier foil 20 is made of aluminum oxide, second insulation layer 42 may be omitted.

~~Essential for~~ In accordance with the present invention is ~~that,~~ first heater supply lead 31 is at a largely constant potential, such as ~~earth~~ ground potential. However, it lies in the discretion of one skilled in the art to connect first heater supply lead 31 to another largely constant potential, for instance if this is more advantageous for reasons of circuit engineering. A largely constant potential of first heater supply lead 31 within the meaning of the present invention is to be understood as a potential that, compared to the potential of second heater supply lead 32, is subject to only slow and/or slight changes and thus does not cause

any, or only low, induced voltages into measuring device 22. That is to say, the induced voltage into measuring device 22 due to potential changes at first heater supply lead 31 is to be considerably lower than the induced voltage that would occur at second heater supply lead 32 due to the potential changes if it were not shielded by first heater supply lead 31, which is at an at least largely constant potential.

~~Summary~~ ABSTRACT

A sensor element ~~(10)~~, having a layer configuration, for detecting a physical property of a gas ~~is proposed~~, in particular for detecting the concentration of a gas component in an exhaust gas of an internal combustion engine. The sensor element ~~(10)~~ has a measuring device~~(22)~~, used to detect a physical property of the gas, and a heating device~~(21)~~. The heating device ~~(21)~~ includes a heater~~(30)~~, which is electrically connected to a first heater supply lead ~~(31)~~ and a second heater supply lead~~(32)~~. The first heater supply lead ~~(31)~~ is arranged in a plane of stratification between the second heater supply lead ~~(32)~~ and the measuring device~~(22)~~. The first heater supply lead ~~(31)~~ is at an at least largely constant electrical potential.

~~(Figure 1)~~